

**SUNDANCE SPAS
PARTS HISTORY
2012-2015**



Table of Contents

2015 880 Series	5
Maxxus	5
Cameo	8
Majesta	9
Altamar.....	10
Marin.....	11
Capri	12
2015 Select Series	13
Victoria	13
Constance	14
2015 780 Series	15
Hamilton	15
Chelsee	16
Certa	17
Montclair	18
Dover	19
2015 680 Series	20
McKinley	20
Ramona	21
Peyton.....	22
Edison.....	23
Tacoma	24
Denali.....	25
2014 880 Series	26
Maxxus	26
Aspen.....	27
Optima	28
Cameo	29
Majesta	30
Altamar.....	31
Marin.....	32
Capri	33
2014 Select Series	34
Victoria	34
Constance.....	35
2014 780 Series	36
Hamilton	36
Chelsee	37
Certa	38
Montclair	39
Dover	40

2014 680 Series	41
Hawthorne.....	41
Hartford.....	42
McKinley.....	43
Ramona.....	44
Peyton.....	45
Edison.....	46
Tacoma.....	47
Denali.....	48
2013 880 Series	49
Maxxus.....	49
Aspen.....	50
Optima.....	51
Cameo.....	52
Majesta.....	53
Altamar.....	54
Marin.....	55
Capri.....	56
2013 Select Series	57
Victoria.....	57
Constance.....	58
2013 780 Series	59
Hamilton.....	59
Chelsea.....	60
Certa.....	61
Camden.....	62
Montclair.....	63
Dover.....	64
2013 680 Series	65
Hawthorne.....	65
Hartford.....	66
Peyton.....	67
Edison.....	68
Tacoma.....	69
Denali.....	70
2012 880 Series	71
Maxxus.....	71
Aspen.....	72
Optima.....	73
Cameo.....	74
Majesta.....	75
Altamar.....	76
Marin.....	77
Capri.....	78
2012 Select Series	79
Victoria.....	79
Constance.....	80

2012 780 Series	81
Hamilton	81
Chelsee	82
Certa	83
Camden	84
Dover	85

2012 680 Series	86
Burlington (With Circ Pump)	86
Burlington (No Circ Pump).....	87
Hawthorne (With Circ Pump)	88
Hawthorne (No Circ Pump).....	89
Hartford (With Circ Pump).....	90
Hartford (No Circ Pump).....	91
Peyton.....	92
Tacoma	93
Denali.....	94

Year:	2015
Model:	Maxxus
Size:	90" x 110" x 41.5" (229 cm x 279.4 cm x 105.41 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 3.1A Processor Board: 6600-392, Processor 3.1A
Transformer:	240V - 12V 6560-274 (pigtailed) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-363 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
65 Stainless Steel Jets:	14-Accu-Pressure (6540-699), 8-Focus Relief (6540-403), 12-Fluidix ST (6540-643, 6541-010), 8-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 2-Whirlpool (6541-564), 2-Fluidix Intelli-Jet (6541-102), 7-Vortex III (6541-111), 6-Pulsator (6540-309, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	8 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-870 (light ring-MiniDin), 4 - 6560-958 (Quad pin lights)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	6 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4), Dual pin lights: 6560-957 (1)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Aspen
Size:	90" x 110" x 41.5" (229 cm x 279.4 cm x 105.41 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 3.1A Processor Board: 6600-392, Processor 3.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-363 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
66 Stainless Steel Jets:	18-Accu-Pressure (6540-699), 12-Fluidix ST (6540-643, 6541-010), 8-Fluidix Nex (6540-500), 14-Fluidix Reflex (6541-169), 2-Whirlpool (6541-564), 6-Fluidix Intelli-Jet (6541-102), 2-Vortex III (6541-111), 4-Pulsator (6540-309, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	8 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-870 (light ring-MiniDin), 4 - 6560-958 (Quad pin lights)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	14 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4), Dual pin lights: 6560-957 (1)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Optima
Size:	89" x 89" x 37.5" (226 cm x 226 cm x 95.25 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.1A Processor Board: 6600-390, Processor 1.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
47 Stainless Steel Jets:	12-Accu-Pressure (6540-699), 16-Fluidix ST (6540-643, 6541-010), 4-Fluidix Nex (6540-500), 1-Whirlpool (6541-564), 5-Fluidix Intelli-Jet (6541-102), 7-Vortex III (6541-111), 2-Pulsator (6540-309, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-870 (light ring-MiniDin), 3 - 6560-958 (Quad pin lights)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	14 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Cameo
Size:	89" x 89" x 37.5" (226 cm x 226 cm x 95.25 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.1A Processor Board: 6600-390, Processor 1.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
54 Stainless Steel Jets:	6-Accu-Pressure (6540-699), 8-Focus Relief (6540-403), 12-Fluidix ST (6540-643, 6541-010), 6-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 4-Whirlpool (6541-564), 2-Fluidix Intelli-Jet (6541-102), 6-Vortex III (6541-111), 4-Pulsator (6540-309, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-870 Llight ring-MiniDin), 3 - 6560-958 (Quad pin lights)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	6 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Majesta
Size:	81" x 86" x 37.5" (206 cm x 218.5 cm x 95.25 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.1A Processor Board: 6600-390, Processor 1.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
31 Stainless Steel Jets:	2-Accu-Pressure (6540-699), 12-Fluidix ST (6540-643, 6541-010), 6-Fluidix Nex (6540-500), 2-Whirlpool (6541-564), 6-Fluidix Intelli-Jet (6541-102), 3-Vortex III (6541-111)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-870 (Light ring-MiniDin), 3 - 6560-958 (Quad pin lights)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	14 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	1 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (2)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Altamar
Size:	81" x 86" x 37.5" (206 cm x 218.5 cm x 95.25 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.1A Processor Board: 6600-390, Processor 1.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
41 Stainless Steel Jets:	6-Focus Relief (6540-403), 12-Fluidix ST (6540-643, 6541-010), 4-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 3-Whirlpool (6541-564), 6-Fluidix Intelli-Jet (6541-102), 2-Vortex III (6541-111), 2-Pulsator (6540-309, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-870 (Light ring-MiniDin), 3 - 6560-958 (Quad pin lights)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	8 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	1 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (2)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Marin
Size:	75" x 91" x 33" (190.5 cm x 231 cm x 84 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.1A Processor Board: 6600-390, Processor 1.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
33 Stainless Steel Jets:	2-Accu-Pressure (6540-699), 2-Focus Relief (6540-403), 10-Fluidix ST (6540-643, 6541-010), 2-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 7-Fluidix Intelli-Jet (6541-102), 2-Vortex III (6541-111), 2-Pulsator (6540-309, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	4 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-870 (Light ring-MiniDin), 2-6560-958 (Quad pin lights)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	10 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	1 integrated
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Capri
Size:	68" x 82" x 30.5" (175.5 cm x 208.5 cm x 77.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.1A Processor Board: 6600-390, Processor 1.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 1-pump main panel Panel: 6600-407
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	N/A
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
28 Stainless Steel Jets:	4-Focus Relief (6540-403), 10-Fluidix ST (6540-643, 6541-010), 2-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 1-Vortex III (6541-111), 3-Fluidix Intelli-Jet (6541-102), 2-Pulsator (6540-309, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	3 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-870 (Light ring-MiniDin), 1-6560-853 (Quad pin lights)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	8 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	1 integrated
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Victoria
Size:	88" x 88" x 36" (223.5 cm x 223.5 cm x 91.5 cm)
Series:	Select
Blower:	N/A
Circuit Board	Select Series Board 6600-726, Eprom REV. 3.61+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6500-402
Panel:	Select Series 2-pump panel 6600-038
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee, curled finger connector
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic timer on circuit board
Circulation Pump:	6500-907
Sanitizer:	ClearRay Water Purification System 6472-853
39 Stainless Steel Jets:	6-Accu-Pressure (6540-699), 6-SMT Micro (6541-787), 4-Fluidix Nex (6540-500), 7-Fluidix ST (6540-643, 6541-010), 9-Fluidix Reflex (6541-169), 4-Fluidix Intelli-Jet (6541-102), 3-Vortex III (6541-111)
Air Controls:	3 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-870 (Light ring-MiniDin), 6540-376 (nut), 6560-958 (Quad pin lights)
Diverter:	1 - 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6455-008
Hand Rails:	2 Integral
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Constance
Size:	88" x 88" x 36" (223.5 cm x 223.5 cm x 91.5 cm)
Series:	Select
Blower:	N/A
Circuit Board	Select Series Board 6600-726, Eprom REV. 3.61
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6500-402
Panel:	Select Series 2-pump panel 6600-038
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee, curled finger connector
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic timer on circuit board
Circulation Pump:	6500-907
Sanitizer:	ClearRay Water Purification System 6472-853
38 Stainless Steel Jets:	12-Accu-Pressure (6540-699), 6-Fluidix Nex (6540-500), 7-Fluidix ST (6540-643, 6541-010), 5-Fluidix Reflex (6541-169), 7-Fluidix Intelli-Jet (6541-102), 1-Vortex III (6541-111)
Air Controls:	4 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-870 (Light ring-MiniDin), 6540-376 (nut), 2 - 6560-958 (Quad pin lights)
Diverter:	1 - 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6455-008
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Hamilton
Size:	89" x 89" x 36" (226.0 cm x 226.0 cm x 91.44 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.61+ Eprom Board 6600-726, Eprom Rev. 3.61+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-063
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
41 Stainless Steel Jets:	9-Accu-Pressure (6541-699), 12-SMT Micro (6541-787), 8-SMT Fluidix (6541-169), 8-Mini Vortex (6541-112), 4-Vortex III (6541-111)
Air Controls:	3 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Chelsee
Size:	89" x 89" x 36" (226.0 cm x 226.0 cm x 91.44 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.61+ Eprom Board 6600-726, Eprom Rev. 3.61+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-063
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
40 Stainless Steel Jets:	17-Accu-Pressure (6541-699), 6-SMT Micro (6541-787), 8-SMT Fluidix (6541-169), 4-Mini Vortex (6541-112), 5-Vortex III (6541-111)
Air Controls:	4 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Certa
Size:	81" x 86" x 36" (206 cm x 218.5 cm x 91.44 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.61+ Eprom Board 6600-726, Eprom Rev. 3.61+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-063
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	1.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
35 Textured Jets:	9-Accu-Pressure (6541-699), 8-SMT Micro (6541-787), 6-SMT Fluidix (6541-169), 8-Mini Vortex (6541-112), 4-Vortex III (6541-111)
Air Controls:	4 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Montclair
Size:	75" x 91" x 33" (191.0 cm x 231.0 cm x 83.82 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.61+ Eprom Board 6600-726, Eprom Rev. 3.61+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-063
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
30 Stainless Steel Jets:	9-Accu-Pressure (6541-699), 4-SMT Micro (6541-787), 6-SMT Fluidix (6541-169), 8-Mini Vortex (6541-112), 3-Vortex III (6541-111)
Air Controls:	3 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	Dover
Size:	69" x 82" x 30.5" (175.3 cm x 208.3 cm x 77.5 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.61+ Eprom Board 6600-724, Eprom Rev. 3.61+
Transformer:	120V - 12V 6560-274 (without) 6000-516 (with plug)
Heater:	1kW 120V/4kW 240V stainless steel tube heater 6500-063
Panel:	780 Series 1-pump panel 6600-189
Pump #1:	1.5HP 2-spd 120V 48F 6500-345 Pump Mount 6000-532
Pump #2:	N/A
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	6560-852
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-855
Circulation Pump:	6500-460
23 Stainless Steel Jets:	9-Accu-Pressure (6541-699), 4-SMT Micro (6541-787), 6-SMT Fluidix (6541-169), 2-Mini Vortex (6541-112), 2-Vortex III (6541-111)
Air Controls:	3 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-359 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2015
Model:	McKinley
Size:	89" x 89" x 36" (226 cm x 226 cm x 91.44 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-720, Eprom Rev. 5.6+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-682
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
44 Stainless Steel Jets:	10-DX (2540-265), 19-DL (2540-255), 2-DVX (2540-433), 6-DXL (2540-319), 6-DVR (2472-610), 1-DST (2540-529)
Air Controls:	4 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2015
Model:	Ramona
Size:	89" x 89" x 36" (226 cm x 226 cm x 91.44 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-720, Eprom Rev. 5.6+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-682
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
45 Stainless Steel Jets:	8-DX (2540-265), 10-DL (2540-255), 4-DVX (2540-433), 12-DXL (2540-319), 4-DV (2540-245), 6-DVR (2472-610), 1-DST (2540-529)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2015
Model:	Peyton
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.44 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-720, Eprom Rev. 5.6+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-682
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
35 Stainless Steel Jets:	4-DX (2540-265), 8-DL (2540-255), 11-DVX (2540-433), 6-DXL (2540-319), 4-DV (2540-245), 2-DXT (6541-652)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	3 - 6472-970
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2015
Model:	Edison
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.44 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-720, Eprom Rev. 5.6+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-682
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
35 Stainless Steel Jets:	4-DX (2540-265), 17-DL (2540-255), 5-DVX (2540-433), 7-DXL (2540-319), 2-DST (2540-529)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2015
Model:	Tacoma
Size:	68" x 68" x 31" (173 cm x 173 cm x 79 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-722, Eprom Rev. 5.6+
Transformer:	120V - 12V 6560-274 (without) 6000-516 (with plug)
Heater:	1 kW 120V or 4.0 kW 240V heater 6000-338
Panel:	1-pump 680 panel 6600-881
Pump #1:	2.5HP 2-spd 240V 48F (6500-345) Pump mount (6000-532)
Pump #2:	N/A
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-159, 6000-742 and 6000-743
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-855
Circulation Pump:	N/A
12 Textured Jets:	4-DVX (2540-431), 8-DXL (2540-317)
Air Controls:	1 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	N/A
Hand Rails:	N/A
Filter:	35 sq ft 6000-136

Year:	2015
Model:	Denali
Size:	78.5" Round x 36" (200.0 cm Round x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-722, Eprom Rev. 5.6+
Transformer:	120V - 12V 6560-274 (without) 6000-516 (with plug)
Heater:	1 kW 120V or 4.0 kW 240V heater 6000-338
Panel:	1-pump 680 panel 6600-881
Pump #1:	2.5HP 2-spd 240V 48F (6500-345) Pump mount (6000-532)
Pump #2:	N/A
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-855
Circulation Pump:	N/A
20 Textured Jets:	8-DX (2540-261), 4-DVX (2540-431), 7-DXL (2540-317), 1-Divert-a-jet (6541-800, 6541-797, 6540-511, 6540-798, 6540-796)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	N/A
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2014
Model:	Maxxus
Size:	90" x 110" x 41.5" (229 cm x 279.5 cm x 105.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 3.1A Processor Board: 6600-392, Processor 3.1A
Transformer:	240V - 12V 6560-274 (pigtails) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-363 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
65 Stainless Steel Jets:	14-Accu-Pressure (6540-699), 8-Focus Relief (6540-403), 12-Fluidix ST (6540-643, 6541-010), 8-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 2-Whirlpool (6541-564), 2-Fluidix Intelli-Jet (6541-102), 7-Vortex III (6541-111), 6-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	8 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	6 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Aspen
Size:	90" x 110" x 41.5" (229 cm x 279.5 cm x 105.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 3.1A Processor Board: 6600-392, Processor 3.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-363 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
66 Stainless Steel Jets:	18-Accu-Pressure (6540-699), 12-Fluidix ST (6540-643, 6541-010), 8-Fluidix Nex (6540-500), 14-Fluidix Reflex (6541-169), 2-Whirlpool (6541-564), 6-Fluidix Intelli-Jet (6541-102), 2-Vortex III (6541-111), 4-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	8 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	14 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Optima
Size:	89" x 89" x 37.5" (226 cm x 226 cm x 95.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.1A Processor Board: 6600-390, Processor 1.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
47 Stainless Steel Jets:	12-Accu-Pressure (6540-699), 16-Fluidix ST (6540-643, 6541-010), 4-Fluidix Nex (6540-500), 1-Whirlpool (6541-564), 5-Fluidix Intelli-Jet (6541-102), 7-Vortex III (6541-111), 2-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	14 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Cameo
Size:	89" x 89" x 37.5" (226 cm x 226 cm x 95.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.1A Processor Board: 6600-390, Processor 1.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
54 Stainless Steel Jets:	6-Accu-Pressure (6540-699), 8-Focus Relief (6540-403), 12-Fluidix ST (6540-643, 6541-010), 6-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 4-Whirlpool (6541-564), 2-Fluidix Intelli-Jet (6541-102), 6-Vortex III (6541-111), 4-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	6 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Majesta
Size:	81" x 86" x 37.5" (206 cm x 218.5 cm x 95.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.1A Processor Board: 6600-390, Processor 1.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
31 Stainless Steel Jets:	2-Accu-Pressure (6540-699), 12-Fluidix ST (6540-643, 6541-010), 6-Fluidix Nex (6540-500), 2-Whirlpool (6541-564), 6-Fluidix Intelli-Jet (6541-102), 3-Vortex III (6541-111)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	14 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	1 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (2)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Altamar
Size:	81" x 86" x 37.5" (206 cm x 218.5 cm x 95.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.1A Processor Board: 6600-390, Processor 1.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
41 Stainless Steel Jets:	6-Focus Relief (6540-403), 12-Fluidix ST (6540-643, 6541-010), 4-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 3-Whirlpool (6541-564), 6-Fluidix Intelli-Jet (6541-102), 2-Vortex III (6541-111), 2-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	8 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	1 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (2)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Marin
Size:	75" x 91" x 33" (190.5 cm x 231 cm x 84 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.1A Processor Board: 6600-390, Processor 1.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
33 Stainless Steel Jets:	2-Accu-Pressure (6540-699), 2-Focus Relief (6540-403), 10-Fluidix ST (6540-643, 6541-010), 2-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 7-Fluidix Intelli-Jet (6541-102), 2-Vortex III (6541-111), 2-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	4 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	10 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	1 integrated
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Capri
Size:	68" x 82" x 30.5" (175.5 cm x 208.5 cm x 77.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.1A Processor Board: 6600-390, Processor 1.1A
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 1-pump main panel Panel: 6600-407
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	N/A
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
28 Stainless Steel Jets:	4-Focus Relief (6540-403), 10-Fluidix ST (6540-643, 6541-010), 2-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 1-Vortex III (6541-111), 3-Fluidix Intelli-Jet (6541-102), 2-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	3 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	8 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	1 integrated
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Victoria
Size:	88" x 88" x 36" (223.5 cm x 223.5 cm x 91.5 cm)
Series:	Select
Blower:	N/A
Circuit Board	Select Series Board 6600-726, Eprom REV. 3.61
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6500-402
Panel:	Select Series 2-pump panel 6600-038
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee, curled finger connector
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic timer on circuit board
Circulation Pump:	6500-907
Sanitizer:	ClearRay Water Purification System 6472-853
39 Stainless Steel Jets:	6-Accu-Pressure (6540-699), 6-SMT Micro (6541-787), 4-Fluidix Nex (6540-500), 7-Fluidix ST (6540-643, 6541-010), 9-Fluidix Reflex (6541-169), 4-Fluidix Intelli-Jet (6541-102), 3-Vortex III (6541-111)
Air Controls:	3 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (Light ring-MiniDin), 6540-376 (nut)
Diverter:	1 - 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6455-008
Hand Rails:	2 Integrated
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) changed mid 2014 Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Constance
Size:	88" x 88" x 36" (223.5 cm x 223.5 cm x 91.5 cm)
Series:	Select
Blower:	N/A
Circuit Board	Select Series Board 6600-726, Eprom REV. 3.61
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6500-402
Panel:	Select Series 2-pump panel 6600-038
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee, curled finger connector
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic timer on circuit board
Circulation Pump:	6500-907
Sanitizer:	ClearRay Water Purification System 6472-853
38 Stainless Steel Jets:	12-Accu-Pressure (6540-699), 6-Fluidix Nex (6540-500), 7-Fluidix ST (6540-643, 6541-010), 5-Fluidix Reflex (6541-169), 7-Fluidix Intelli-Jet (6541-102), 1-Vortex III (6541-111)
Air Controls:	4 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (Light ring-MiniDin), 6540-376 (nut)
Diverter:	1 - 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6455-008
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) changed mid 2014 Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Hamilton
Size:	89" x 89" x 36" (226.06 cm x 226.06 cm x 91.5 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.61+ Eprom Board 6600-726, Eprom Rev. 3.61+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-063
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
41 Stainless Steel Jets:	9-Accu-Pressure (6541-700), 12-SMT Micro (6541-787), 8-SMT Fluidix (6541-169), 8-Mini Vortex (6541-112), 4-Vortex III (6541-111)
Air Controls:	3 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Chelsee
Size:	89" x 89" x 36" (226.06 cm x 226.06 cm x 91.5 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.61+ Eprom Board 6600-726, Eprom Rev. 3.61+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-063
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
40 Stainless Steel Jets:	17-Accu-Pressure (6541-700), 6-SMT Micro (6541-787), 8-SMT Fluidix (6541-169), 4-Mini Vortex (6541-112), 5-Vortex III (6541-111)
Air Controls:v	4 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Certa
Size:	81" x 86" x 36" (203 cm x 218.5 cm x 91.44 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.61+ Eprom Board 6600-726, Eprom Rev. 3.61+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-063
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	1.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
35 Textured Jets:	9-Accu-Pressure (6541-700), 8-SMT Micro (6541-787), 6-SMT Fluidix (6541-169), 8-Mini Vortex (6541-112), 4-Vortex III (6541-111)
Air Controls:	4 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Montclair
Size:	75" x 91" x 33" (190.5 cm x 231.14 cm x 83.82 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.61+ Eprom Board 6600-726, Eprom Rev. 3.61+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-063
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
30 Stainless Steel Jets:	9-Accu-Pressure (6541-700), 4-SMT Micro (6541-787), 6-SMT Fluidix (6541-169), 8-Mini Vortex (6541-112), 3-Vortex III (6541-111)
Air Controls:	3 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2014
Model:	Dover
Size:	69" x 82" x 30.5" (175.26 cm x 208.28 cm x 77.47 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.60+ Eprom Board 6600-044, Eprom Rev. 3.60+
Transformer:	120V - 12V 6560-274 (without) 6000-516 (with plug)
Heater:	1kW 120V/4kW 240V stainless steel tube heater 6500-063
Panel:	780 Series 1-pump panel 6600-189
Pump #1:	1.5HP 2-spd 120V 48F 6500-345 Pump Mount 6000-532
Pump #2:	N/A
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	6560-852
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-855
Circulation Pump:	6500-460
23 Stainless Steel Jets:	9-Accu-Pressure (6541-700), 4-SMT Micro (6541-787), 6-SMT Fluidix (6541-169), 2-Mini Vortex (6541-112), 2-Vortex III (6541-111)
Air Controls:	3 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2014 (till 05/2014)
Model:	Hawthorne
Size:	92" x 92" x 36" (234 cm x 234 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-720, Eprom Rev. 5.6+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6000-156
Panel:	2-pump 680 panel 6600-682
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	New style weir gate 6540-901
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
44 Stainless Steel Jets:	8-DX (2540-265), 10-DL (2540-255), 10-DVX (2540-433), 11-DXL (2540-319), 4-DV (2540-245), 1-DST (2540-529)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	2 - 45 sq ft 373043S

Year:	2014 (till 05/2014)
Model:	Hartford
Size:	88" x 88" x 36" (223.5 cm x 223.5 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-720, Eprom Rev. 5.6+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-682
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	New style weir gate 6540-901
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6000-125
42 Stainless Steel Jets:	10-DX (2540-265), 15-DL (2540-255), 10-DVX (2540-433), 6-DXL (2540-319), 1-DST (2540-529)
Air Controls:	4 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	2 - 45 sq ft 373043S

Year:	2014 (06/2014+)
Model:	McKinley
Size:	89" x 89" x 36" (226 cm x 226 cm x 91.44 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-720, Eprom Rev. 5.6+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-682
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
44 Stainless Steel Jets:	10-DX (2540-265), 19-DL (2540-255), 2-DVX (2540-433), 6-DXL (2540-319), 6-DVR (2472-610), 1-DST (2540-529)
Air Controls:	4 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2014 (06/2014+)
Model:	Ramona
Size:	89" x 89" x 36" (226 cm x 226 cm x 91.44 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-720, Eprom Rev. 5.6+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-682
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
45 Stainless Steel Jets:	8-DX (2540-265), 10-DL (2540-255), 4-DVX (2540-433), 12-DXL (2540-319), 4-DV (2540-245), 6-DVR (2472-610), 1-DST (2540-529)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2014
Model:	Peyton
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-720, Eprom Rev. 5.6+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-682
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
35 Stainless Steel Jets:	4-DX (2540-265), 8-DL (2540-255), 11-DVX (2540-433), 6-DXL (2540-319), 4-DV (2540-245), 2-DXT (6541-652)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	3 - 6472-970
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2014
Model:	Edison
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-720, Eprom Rev. 5.6+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-682
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
35 Stainless Steel Jets:	4-DX (2540-265), 17-DL (2540-255), 5-DVX (2540-433), 7-DXL (2540-319), 2-DST (2540-529)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2014
Model:	Tacoma
Size:	68" x 68" x 31" (173 cm x 173 cm x 79 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-722, Eprom Rev. 5.6+
Transformer:	120V - 12V 6560-274 (without) 6000-516 (with plug)
Heater:	1 kW 120V or 4.0 kW 240V heater 6000-338
Panel:	1-pump 680 panel 6600-881
Pump #1:	2.5HP 2-spd 240V 48F (6500-345) Pump mount (6000-532)
Pump #2:	N/A
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-159, 6000-742 and 6000-743
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-855
Circulation Pump:	N/A
12 Textured Jets:	4-DVX (2540-431), 8-DXL (2540-317)
Air Controls:	1 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	N/A
Hand Rails:	N/A
Filter:	35 sq ft 6000-136

Year:	2014
Model:	Denali
Size:	78" Round x 36" (198.1 cm Round x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.6+ Eprom Board 6600-722, Eprom Rev. 5.6+
Transformer:	120V - 12V 6560-274 (without) 6000-516 (with plug)
Heater:	1 kW 120V or 4.0 kW 240V heater 6000-338
Panel:	1-pump 680 panel 6600-881
Pump #1:	2.5HP 2-spd 240V 48F (6500-345) Pump mount (6000-532)
Pump #2:	N/A
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-855
Circulation Pump:	N/A
20 Textured Jets:	8-DX (2540-261), 4-DVX (2540-431), 7-DXL (2540-317), 1-Divert-a-jet (6541-800, 6541-797, 6540-511, 6540-798, 6540-796)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	N/A
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2013
Model:	Maxxus
Size:	90" x 110" x 41.5" (229 cm x 279.5 cm x 105.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 3.0B Processor Board: 6600-398, Processor 3.0B
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-363 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
65 Stainless Steel Jets*:	14-Accu-Pressure (6540-699), 8-Focus Relief (6540-403), 12-Fluidix ST (6540-643, 6541-010), 8-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 2-Whirlpool (6541-564), 2-Fluidix Intelli-Jet (6541-102), 7-Vortex III (6541-111), 6-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	8 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	6 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

*Verify Pulsator jet. Two styles used in 2013, not interchangeable.

Year:	2013
Model:	Aspen
Size:	90" x 110" x 41.5" (229 cm x 279.5 cm x 105.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 3.0B Processor Board: 6600-398, Processor 3.0B
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-363 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
66 Stainless Steel Jets*:	18-Accu-Pressure (6540-699), 12-Fluidix ST (6540-643, 6541-010), 8-Fluidix Nex (6540-500), 14-Fluidix Reflex (6541-169), 2-Whirlpool (6541-564), 6-Fluidix Intelli-Jet (6541-102), 2-Vortex III (6541-111), 4-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	8 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	14 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

*Verify Pulsator jet. Two styles used, not interchangeable.

Year:	2013
Model:	Optima
Size:	89" x 89" x 37.5" (226 cm x 226 cm x 95.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.0i Processor Board: 6600-176, Processor 1.0i
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
47 Stainless Steel Jets*:	12-Accu-Pressure (6540-699), 16-Fluidix ST (6540-643, 6541-010), 4-Fluidix Nex (6540-500), 1-Whirlpool (6541-564), 5-Fluidix Intelli-Jet (6541-102), 7-Vortex III (6541-111), 2-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	14 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

*Verify Pulsator jet. Two styles used, not interchangeable.

Year:	2013
Model:	Cameo
Size:	89" x 89" x 37.5" (226 cm x 226 cm x 95.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.0i Processor Board: 6600-176, Processor 1.0i
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
54 Stainless Steel Jets*:	6-Accu-Pressure (6540-699), 8-Focus Relief (6540-403), 12-Fluidix ST (6540-643, 6541-010), 6-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 4-Whirlpool (6541-564), 2-Fluidix Intelli-Jet (6541-102), 6-Vortex III (6541-111), 4-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	6 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

*Verify Pulsator jet. Two styles used, not interchangeable.

Year:	2013
Model:	Majesta
Size:	81" x 86" x 37.5" (206 cm x 218.5 cm x 95.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.0i Processor Board: 6600-176, Processor 1.0i
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
31 Stainless Steel Jets:	2-Accu-Pressure (6540-699), 12-Fluidix ST (6540-643, 6541-010), 6-Fluidix Nex (6540-500), 2-Whirlpool (6541-564), 6-Fluidix Intelli-Jet (6541-102), 3-Vortex III (6541-111)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	14 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	1 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (2)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2013
Model:	Altamar
Size:	81" x 86" x 37.5" (206 cm x 218.5 cm x 95.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.0i Processor Board: 6600-176, Processor 1.0i
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
41 Stainless Steel Jets*:	6-Focus Relief (6540-403), 12-Fluidix ST (6540-643, 6541-010), 4-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 3-Whirlpool (6541-564), 6-Fluidix Intelli-Jet (6541-102), 2-Vortex III (6541-111), 2-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	8 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	1 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (2)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

*Verify Pulsator jet. Two styles used, not interchangeable.

Year:	2013
Model:	Marin
Size:	75" x 91" x 33" (190.5 cm x 231 cm x 84 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.0i Processor Board: 6600-176, Processor 1.0i
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-425
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
33 Stainless Steel Jets*:	2-Accu-Pressure (6540-699), 2-Focus Relief (6540-403), 10-Fluidix ST (6540-643, 6541-010), 2-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 7-Fluidix Intelli-Jet (6541-102), 2-Vortex III (6541-111), 2-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540-338, 6660-002)
Air Controls:	4 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	10 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	1 integrated
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

*Verify Pulsator jet. Two styles used, not interchangeable.

Year:	2013
Model:	Capri
Size:	68" x 82" x 30.5" (175.5 cm x 208.5 cm x 77.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.0i Processor Board: 6600-176, Processor 1.0i
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 1-pump main panel Panel: 6600-407
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	N/A
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
28 Stainless Steel Jets*:	4-Focus Relief (6540-403), 10-Fluidix ST (6540-643, 6541-010), 2-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 1-Vortex III (6541-111), 3-Fluidix Intelli- Jet (6541-102), 2-Pulsator (6540-308, 6540-336, 6540-343, 6540-330, 6540- 338, 6660-002)
Air Controls:	3 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203 (light ring-MiniDin)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	8 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	1 integrated
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473- 164S or Standard Filter 6540-488S (125 sq ft)

*Verify Pulsator jet. Two styles used, not interchangeable.

Year:	2013
Model:	Victoria
Size:	88" x 88" x 36" (223.5 cm x 223.5 cm x 91.5 cm)
Series:	Select
Blower:	N/A
Circuit Board	Select Series Board 6000-167, Eprom REV. 3.60
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6500-402
Panel:	Select Series 2-pump panel 6600-185
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee, curled finger connector
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic timer on circuit board
Circulation Pump:	6500-907
Sanitizer:	ClearRay Water Purification System 6472-853
39 Stainless Steel Jets:	6-Accu-Pressure (6540-699), 6-SMT Micro (6541-787), 4-Fluidix Nex (6540-500), 7-Fluidix ST (6540-643, 6541-010), 9-Fluidix Reflex (6541-169), 4-Fluidix Intelli-Jet (6541-102), 3-Vortex III (6541-111)
Air Controls:	3 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203* (Light ring-MiniDin), 6540-376 (nut) *changed from 6540-616 mid 2013
Diverter:	1 - 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6455-008
Hand Rails:	2 Integral
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-089 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2013
Model:	Constance
Size:	88" x 88" x 36" (223.5 cm x 223.5 cm x 91.5 cm)
Series:	Select
Blower:	N/A
Circuit Board	Select Series Board 6000-167, Eprom REV. 3.60
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6500-402
Panel:	Select Series 2-pump panel 6600-185
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee, curled finger connector
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic timer on circuit board
Circulation Pump:	6500-907
Sanitizer:	ClearRay Water Purification System 6472-853
38 Stainless Steel Jets:	12-Accu-Pressure (6540-699), 6-Fluidix Nex (6540-500), 7-Fluidix ST (6540-643, 6541-010), 5-Fluidix Reflex (6541-169), 7-Fluidix Intelli-Jet (6541-102), 1-Vortex III (6541-111)
Air Controls:	4 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6560-203* (Light ring-MiniDin), 6540-376 (nut) *changed from 6540-616 mid 2013
Diverter:	1 - 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6455-008
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-089 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2013
Model:	Hamilton
Size:	89" x 89" x 36" (226.06 cm x 226.06 cm x 91.5 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-187
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907 started 05/2013 (prior to that P/N 6000-125 was used)
41 Stainless Steel Jets:	9-Accu-Pressure (6541-700), 12-SMT Micro (6541-787), 8-SMT Fluidix (6541-169), 8-Mini Vortex (6541-112), 4-Vortex III (6541-111)
Air Controls:	3 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2013
Model:	Chelsee
Size:	89" x 89" x 36" (226.06 cm x 226.06 cm x 91.5 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-187
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907 started 05/2013 (prior to that P/N 6000-125 was used)
40 Stainless Steel Jets:	17-Accu-Pressure (6541-700), 6-SMT Micro (6541-787), 8-SMT Fluidix (6541-169), 4-Mini Vortex (6541-112), 5-Vortex III (6541-111)
Air Controls:	4 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2013
Model:	Certa
Size:	81" x 86" x 36" (203 cm x 218.5 cm x 91.44 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-187
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	1.5HP 1-spd 240V 56F 6500-369 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907 started 05/2013 (prior to that P/N 6000-125 was used)
35 Stainless Steel Jets:	9-Accu-Pressure (6541-700), 8-SMT Micro (6541-787), 6-SMT Fluidix (6541-169), 8-Mini Vortex (6541-112), 4-Vortex III (6541-111)
Air Controls:	4 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2013 (up to 03/2013)
Model:	Camden
Size:	76" x 83" x 34" (193 cm x 211 cm x 86.5 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 1-pump panel 6600-881
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	N/A
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6000-125
24 Textured Jets:	9-Accu-Pressure (6541-695), 4-SMT Micro (6540-961), 2-SMT Fluidix (6541-119), 6-SMT Mini (6540-960), 3-SMT (6540-755)
Air Controls:	4 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (light control-ribbon), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2013 (began 04/2013)
Model:	Montclair
Size:	75" x 91" x 33" (190.5 cm x 231.14 cm x 83.82 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-187
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
30 Stainless Steel Jets:	9-Accu-Pressure (6541-700), 4-SMT Micro (6541-787), 6-SMT Fluidix (6541-169), 8-Mini Vortex (6541-112), 3-Vortex III (6541-111)
Air Controls:	3 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2013
Model:	Dover
Size:	69" x 82" x 30.5" (175.26 cm x 208.28 cm x 77.47 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.60+ Eprom Board 6600-044, Eprom Rev. 3.60+
Transformer:	120V - 12V 6560-274 (without) 6000-516 (with plug)
Heater:	1kW 120V/4kW 240V stainless steel tube heater 6500-063
Panel:	780 Series 1-pump panel 6600-189
Pump #1:	1.5HP 2-spd 120V 48F 6500-345 Pump Mount 6000-532
Pump #2:	N/A
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	6560-852
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-855
Circulation Pump:	6500-460
23 Stainless Steel Jets:	9-Accu-Pressure (6541-700), 4-SMT Micro (6541-787), 6-SMT Fluidix (6541-169), 2-Mini Vortex (6541-112), 2-Vortex III (6541-111)
Air Controls:	3 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2013
Model:	Hawthorne
Size:	92" x 92" x 36" (234 cm x 234 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.57+ Eprom Board 6600-044, Eprom Rev. 5.57+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6000-156
Panel:	2-pump 680 panel 6600-671 (used till 05/2013) 6600-682 (used from 06/2013+)
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	New style weir gate 6540-901
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
44 Stainless Steel Jets:	8-DX (2540-265), 10-DL (2540-255), 10-DVX (2540-433), 11-DXL (2540-319), 4-DV (2540-245), 1-DST (2540-529)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	2 - 45 sq ft 373043S

Year:	2013
Model:	Hartford
Size:	88" x 88" x 36" (223.5 cm x 223.5 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.57+ Eprom Board 6600-044, Eprom Rev. 5.57+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-671 (used till 05/2013) 6600-682 (used from 06/2013+)
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	New style weir gate 6540-901
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
42 Stainless Steel Jets:	10-DX (2540-265), 15-DL (2540-255), 10-DVX (2540-433), 6-DXL (2540-319), 1-DST (2540-529)
Air Controls:	4 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	2 - 45 sq ft 373043S

Year:	2013
Model:	Peyton
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.59+ Eprom Board 6600-046, Eprom Rev. 5.59+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-671 (used till 05/2013) 6600-682 (used from 06/2013+)
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
35 Stainless Steel Jets:	4-DX (2540-265), 8-DL (2540-255), 11-DVX (2540-433), 6-DXL (2540-319), 4-DV (2540-245), 2-DXT (6541-652)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	3 - 6472-970
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2013
Model:	Edison
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.59+ Eprom Board 6600-046, Eprom Rev. 5.59+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-682
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
35 Stainless Steel Jets:	4-DX (2540-265), 17-DL (2540-255), 5-DVX (2540-433), 7-DXL (2540-319), 2-DST (2540-529)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2013
Model:	Tacoma
Size:	68" x 68" x 31" (173 cm x 173 cm x 79 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.59+ Eprom Board 6600-042, Eprom Rev. 5.59+
Transformer:	120V - 12V 6560-274 (without) 6000-516 (with plug)
Heater:	1 kW 120V or 4.0 kW 240V heater 6000-338
Panel:	1-pump 680 panel 6600-652 (used till 05/2013) 6600-881 (used from 06/2013+)
Pump #1:	2.5HP 2-spd 240V 48F (6500-345) Pump mount (6000-532)
Pump #2:	N/A
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-159, 6000-742 and 6000-743
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-855
Circulation Pump:	N/A
12 Textured Jets:	4-DVX (2540-431), 8-DXL (2540-317)
Air Controls:	1 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	N/A
Hand Rails:	N/A
Filter:	35 sq ft 6000-136

Year:	2013
Model:	Denali
Size:	78" Round x 36" (198.1 cm Round x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.59+ Eprom Board 6600-042, Eprom Rev. 5.59+
Transformer:	120V - 12V 6560-274 (without) 6000-516 (with plug)
Heater:	1 kW 120V or 4.0 kW 240V heater 6000-338
Panel:	1-pump 680 panel 6600-652 (used till 05/2013) 6600-881 (used from 06/2013+)
Pump #1:	2.5HP 2-spd 240V 48F (6500-345) Pump mount (6000-532)
Pump #2:	N/A
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-855
Circulation Pump:	N/A
20 Textured Jets:	8-DX (2540-261), 4-DVX (2540-431), 7-DXL (2540-317), 1-Divert-a-jet (6541-800, 6541-797, 6540-511, 6540-798, 6540-796)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	N/A
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2012
Model:	Maxxus
Size:	90" x 110" x 41.5" (229 cm x 279.5 cm x 105.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 3.0B Processor Board: 6600-398, Processor 3.0B
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-882 (used till 05/2012) 6600-854 (from 06-12/2012)
Pump #1:	2.5HP 1-spd 240V 56F 6500-363 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
65 Stainless Steel Jets:	14-Accu-Pressure (6540-699), 6-Pulsator (6541-513), 8-Focus Relief (6540-403), 12-Fluidix ST (6540-643, 6541-010), 8-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 2-Whirlpool (6541-564), 2-Fluidix Intelli-Jet (6541-102), 7-Vortex (6000-166)
Air Controls:	8 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (light ring-ribbon)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	6 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Aspen
Size:	90" x 110" x 41.5" (229 cm x 279.5 cm x 105.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 3.0B Processor Board: 6600-398, Processor 3.0B
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-882 (used till 05/2012) 6600-854 (from 06-12/2012)
Pump #1:	2.5HP 1-spd 240V 56F 6500-363 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
66 Stainless Steel Jets:	18-Accu-Pressure (6540-699), 4-Pulsator (6541-513), 12-Fluidix ST (6540-643, 6541-010), 8-Fluidix Nex (6540-500), 14-Fluidix Reflex (6541-169), 2-Whirlpool (6541-564), 6-Fluidix Intelli-Jet (6541-102), 2-Vortex (6000-166)
Air Controls:	8 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (light ring-ribbon)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	14 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Optima
Size:	89" x 89" x 37.5" (226 cm x 226 cm x 95.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.0i Processor Board: 6600-176, Processor 1.0i
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-882 (used till 05/2012) 6600-854 (from 06-12/2012)
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
47 Stainless Steel Jets:	12-Accu-Pressure (6540-699), 2-Pulsator (6541-513), 16-Fluidix ST (6540-643, 6541-010), 4-Fluidix Nex (6540-500), 1-Whirlpool (6541-564), 5-Fluidix Intelli-Jet (6541-102), 7-Vortex (6000-166)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (light ring-ribbon)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	14 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Cameo
Size:	89" x 89" x 37.5" (226 cm x 226 cm x 95.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.0i Processor Board: 6600-176, Processor 1.0i
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-882 (used till 05/2012) 6600-854 (from 06-12/2012)
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
54 Stainless Steel Jets:	6-Accu-Pressure (6540-699), 4-Pulsator (6541-513), 8-Focus Relief (6540-403), 12-Fluidix ST (6540-643, 6541-010), 6-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 4-Whirlpool (6541-564), 2-Fluidix Intelli-Jet (6541-102), 6-Vortex (6000-166)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (light ring-ribbon)
Diverter:	2 - (3-way valves) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	6 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	2 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (4)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473- 164S or Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Majesta
Size:	81" x 86" x 37.5" (206 cm x 218.5 cm x 95.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.0i Processor Board: 6600-176, Processor 1.0i
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-882 (used till 05/2012) 6600-854 (from 06-12/2012)
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
31 Stainless Steel Jets:	2-Accu-Pressure (6540-699), 12-Fluidix ST (6540-643, 6541-010), 6-Fluidix Nex (6540-500), 2-Whirlpool (6541-564), 6-Fluidix Intelli-Jet (6541-102), 3-Vortex (6000-166)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (light ring-ribbon)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	14 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	1 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (2)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Altamar
Size:	81" x 86" x 37.5" (206 cm x 218.5 cm x 95.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.0i Processor Board: 6600-176, Processor 1.0i
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-882 (used till 05/2012) 6600-854 (from 06-12/2012)
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
41 Stainless Steel Jets:	2-Pulsator (6541-513), 6-Focus Relief (6540-403), 12-Fluidix ST (6540-643, 6541-010), 4-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 3-Whirlpool (6541-564), 6-Fluidix Intelli-Jet (6541-102), 2-Vortex (6000-166)
Air Controls:	5 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (light ring-ribbon)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	8 - 6541-253
Pillows	3 - 6472-964
Hand Rails:	1 High quality stainless steel handles Rail: 6570-512, Grommets: 6540-651 (2)
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Marin
Size:	75" x 91" x 33" (190.5 cm x 231 cm x 84 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.0i Processor Board: 6600-176, Processor 1.0i
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 2-pump main panel Panel: 6600-882 (used till 05/2012) 6600-854 (from 06-12/2012)
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
33 Stainless Steel Jets:	2-Accu-Pressure (6540-699), 2-Pulsator (6541-513), 2-Focus Relief (6540-403), 10-Fluidix ST (6540-643, 6541-010), 2-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 7-Fluidix Intelli-Jet (6541-102), 2-Vortex (6000-166)
Air Controls:	4 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (light ring-ribbon)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	10 - 6541-253
Pillows	4 - 6472-964
Hand Rails:	1 integrated
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Capri
Size:	68" x 82" x 30.5" (175.5 cm x 208.5 cm x 77.5 cm)
Series:	880
Blower:	1HP 240V blower motor assembly 6500-148
Board:	880 Series circuit board with 1.0i Processor Board: 6600-176, Processor 1.0i
Transformer:	240V - 12V 6560-274 (without) 6000-515 (with plug)
Heater:	"Smart Heater" - plastic housing with titanium element, 5.5kW, 240V 6500-310
Panel:	880 1-pump main panel Panel: 6600-865
Pump #1:	2.5HP 1-spd 240V 56F 6500-352 Mounting Bracket 6000-535
Pump #2:	N/A
Pump #3:	N/A
Timer:	Battery +3V CR2032
Temp Sensor:	Boxed end connector, thermistor type, resistance can be checked 6600-167
Hi-Limit:	Boxed end connector, thermistor type, resistance can be checked 6600-168
Flow Switch	6560-860, Flow switch with transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6500-907
28 Stainless Steel Jets:	2-Pulsator (6541-513), 4-Focus Relief (6540-403), 10-Fluidix ST (6540-643, 6541-010), 2-Fluidix Nex (6540-500), 6-Fluidix Reflex (6541-169), 3-Fluidix Intelli-Jet (6541-102), 1-Vortex (6000-166)
Air Controls:	3 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-375 (air control jacket)
Diverter:	1 - (3-way valve) 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	8 - 6541-253
Pillows	3 - 6472-960
Hand Rails:	1 integrated
Filter:	MicroClean Ultra Filter 6541-397S (130 sq ft), Outer 6473-165S, Inner 6473-164S or Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Victoria
Size:	88" x 88" x 36" (223.5 cm x 223.5 cm x 91.5 cm)
Series:	Select
Blower:	N/A
Circuit Board	Select Series Board 6000-167, Eprom REV. 3.60
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6500-402
Panel:	Select Series 2-pump panel 6600-016
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee, curled finger connector
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic timer on circuit board
Circulation Pump:	6500-907
Sanitizer:	ClearRay Water Purification System 6472-853
39 Stainless Steel Jets:	6-Accu-Pressure (6540-699), 6-SMT Micro (6541-787), 4-Fluidix Nex (6540-500), 7-Fluidix ST (6540-643, 6541-010), 9-Fluidix Reflex (6541-169), 4-Fluidix Intelli-Jet (6541-102), 3-Vortex (6000-166)
Air Controls:	3 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (Light ring-ribbon), 6540-376 (nut)
Diverter:	1 - 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6455-008
Hand Rails:	2 Integral
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-089 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Constance
Size:	88" x 88" x 36" (223.5 cm x 223.5 cm x 91.5 cm)
Series:	Select
Blower:	N/A
Circuit Board	Select Series Board 6000-167, Eprom REV. 3.60
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6500-402
Panel:	Select Series 2-pump panel 6600-016
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee, curled finger connector
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic timer on circuit board
Circulation Pump:	6500-907
Sanitizer:	ClearRay Water Purification System 6472-853
38 Stainless Steel Jets:	12-Accu-Pressure (6540-699), 6-Fluidix Nex (6540-500), 7-Fluidix ST (6540-643, 6541-010), 5-Fluidix Reflex (6541-169), 7-Fluidix Intelli-Jet (6541-102), 1-Vortex (6000-166)
Air Controls:	4 - 6000-188 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (Light ring-ribbon), 6540-376 (nut)
Diverter:	1 - 6540-533 (knob), 6541-377 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6455-008
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-089 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Hamilton
Size:	88" x 88" x 36" (223.54 cm x 223.5 cm x 91.5 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-880
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6000-125
40 Textured Jets:	9-Accu-Pressure (6541-695), 12-SMT Micro (6540-961), 8-SMT Fluidix (6541-119), 11-SMT (6540-755)
Air Controls:	3 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (light ring-ribbon), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Chelsee
Size:	88" x 88" x 36" (223.54 cm x 223.5 cm x 91.5 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-880
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	2.5HP 1-spd 240V 56F 6500-352 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6000-125
36 Textured Jets:	9-Accu-Pressure (6541-695), 8-SMT Micro (6540-961), 2-SMT Fluidix (6541-119), 4-SMT Mini (6540-960), 12-SMT (6540-755), 1-SMT Turbo (6540-771)
Air Controls:	4 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (light ring-ribbon), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Certa
Size:	81" x 86" x 37.5" (206 cm x 218.5 cm x 92.25 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 2-pump panel 6600-880
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2 (till 10/2012):	1.5HP 1-spd 240V 48F 6500-351 Pump Mount 6000-532
Pump #2 (11/2012):	1.5HP 1-spd 240V 56F 6500-369 Pump Mount 6000-535
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6000-125
35 Textured Jets:	9-Accu-Pressure (6541-695), 8-SMT Micro (6540-961), 8-SMT Fluidix (6541-119), 10-SMT (6540-755)
Air Controls:	4 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (light ring-ribbon), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Camden
Size:	76" x 83" x 34" (193 cm x 211 cm x 86.5 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5kW 240V stainless steel tube heater 6500-402
Panel:	780 Series 1-pump panel 6600-881
Pump #1:	2.5HP 2-spd 240V 56F 6500-367 Pump Mount 6000-535
Pump #2:	N/A
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	2560-040, Flow switch in a transparent tee
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6000-125
24 Textured Jets:	9-Accu-Pressure (6541-695), 4-SMT Micro (6540-961), 2-SMT Fluidix (6541-119), 6-SMT Mini (6540-960), 3-SMT (6540-755)
Air Controls:	4 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (light ring-ribbon), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2012
Model:	Dover
Size:	69" x 82" x 30.5" (175.26 cm x 208.28 cm x 77.47 cm)
Series:	780
Blower:	N/A
Board:	780 Series with 3.60+ Eprom Board 6600-044, Eprom Rev. 3.60+
Transformer:	120V - 12V 6560-274 (without) 6000-516 (with plug)
Heater:	1kW 120V/4kW 240V stainless steel tube heater 6500-063
Panel:	780 Series 1-pump panel 6600-881
Pump #1:	1.5HP 2-spd 120V 48F 6500-345 Pump Mount 6000-532
Pump #2:	N/A
Temp Sensor:	Curled finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch	6560-852
Weir Gate:	New style sliding weir gate 6540-882
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-855
Circulation Pump:	6500-460
22 Textured Jets:	9-Accu-Pressure (6541-695), 2-SMT Micro (6540-961), 6-SMT Fluidix (6541-119), 5-SMT (6540-755)
Air Controls:	3 - 6540-361 (knob/cap), 6540-377 (body/stem), 6540-522 (O-ring), 6540-616 (Light ring-ribbon), 6540-376 (nut)
Diverter:	1 - 6540-363 (knob), 6540-362 (cap), 6540-865 (body o-ring), 6540-868 (stem o-ring), 6570-248 (washer), 6540-966 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-966
Hand Rails:	N/A
Filter:	MicroClean I 6540-501S (75 sq ft) and 6540-502 (50 sq ft) Standard Filter 6540-488S (125 sq ft)

Year:	2012 (01/12-03/12)
Model:	Burlington (With Circ Pump)
Size:	81" x 86" x 37.5" (206 cm x 218.5 cm x 95.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6500-402
Panel:	1-pump 680 panel 6600-652
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch:	2560-040, Flow Switch in a transparent tee
Weir Gate:	New style weir gate 6540-901
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6000-125
44 Stainless Steel Jets:	2-DX (2540-265), 6-DL (2540-255), 7-DVX (2540-433), 10-DXL (2540-319)
Air Controls:	4 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-970
Hand Rails:	N/A
Filter:	2 - 45 sq ft 373043S

Year:	2012 (01/12-03/12)
Model:	Burlington (No Circ Pump)
Size:	81" x 86" x 37.5" (206 cm x 218.5 cm x 95.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	1-pump 680 panel 6600-652
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	New style weir gate 6540-901
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
44 Stainless Steel Jets:	2-DX (2540-265), 6-DL (2540-255), 7-DVX (2540-433), 10-DXL (2540-319)
Air Controls:	4 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	3 - 6472-970
Hand Rails:	N/A
Filter:	2 - 45 sq ft 373043S

Year:	2012
Model:	Hawthorne (With Circ Pump)
Size:	92" x 92" x 36" (234 cm x 234 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6500-402
Panel:	2-pump 680 panel 6600-671
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch:	2560-040, Flow Switch in a transparent tee
Weir Gate:	New style weir gate 6540-901
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6000-125
44 Stainless Steel Jets:	8-DX (2540-265), 10-DL (2540-255), 10-DVX (2540-433), 11-DXL (2540-319), 4-DV (2540-245), 1-DST (2540-529)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	2 - 45 sq ft 373043S

Year:	2012
Model:	Hawthorne (No Circ Pump)
Size:	92" x 92" x 36" (234 cm x 234 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.57+ Eprom Board 6600-044, Eprom Rev. 5.57+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6000-156
Panel:	2-pump 680 panel 6600-671
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	New style weir gate 6540-901
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
44 Stainless Steel Jets:	8-DX (2540-265), 10-DL (2540-255), 10-DVX (2540-433), 11-DXL (2540-319), 4-DV (2540-245), 1-DST (2540-529)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	2 - 45 sq ft 373043S

Year:	2012
Model:	Hartford (With Circ Pump)
Size:	88" x 88" x 36" (223.5 cm x 223.5 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 3.60+ Eprom Board 6000-167, Eprom Rev. 3.60+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel tube heater 6500-402
Panel:	2-pump 680 panel 6600-671
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Flow Switch:	2560-040, Flow Switch in a transparent tee
Weir Gate:	New style weir gate 6540-901
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6000-125
42 Stainless Steel Jets:	10-DX (2540-265), 15-DL (2540-255), 10-DVX (2540-433), 6-DXL (2540-319), 1-DST (2540-529)
Air Controls:	4 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	2 - 45 sq ft 373043S

Year:	2012
Model:	Hartford (No Circ Pump)
Size:	88" x 88" x 36" (223.5 cm x 223.5 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.57+ Eprom Board 6600-044, Eprom Rev. 5.57+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-671
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	New style weir gate 6540-901
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	6000-125
42 Stainless Steel Jets:	10-DX (2540-265), 15-DL (2540-255), 10-DVX (2540-433), 6-DXL (2540-319), 1-DST (2540-529)
Air Controls:	4 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	1 - 2540-239 (knob/cap), 6541-241 (stem o-ring 2x), 6541-240 (body o-ring), 6541-242 (gate)
Air Injectors:	N/A
Pillows	4 - 6472-970
Hand Rails:	N/A
Filter:	2 - 45 sq ft 373043S

Year:	2012 (started in 04/2012)
Model:	Peyton
Size:	84" x 84" x 36" (213.5 cm x 213.5 cm x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.59+ Eprom Board 6600-046, Eprom Rev. 5.59+
Transformer:	240V - 12V 6560-274 (without) 6000-517 (with plug)
Heater:	5.5 kW 240V stainless steel heater 6000-156
Panel:	2-pump 680 panel 6600-671
Pump #1:	2.5HP 2-spd 240V 56F (6500-367) Pump mount (6000-535)
Pump #2:	2.5HP 1-spd 240V 56F (6500-352) Pump mount (6000-535)
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-853
Circulation Pump:	N/A
35 Stainless Steel Jets:	4-DX (2540-265), 8-DL (2540-255), 11-DVX (2540-433), 6-DXL (2540-319), 4-DV (2540-245), 2-DXT (6541-652)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	3 - 6472-970
Hand Rails:	N/A
Filter:	50 sq ft 373045S

Year:	2012
Model:	Tacoma
Size:	68" x 68" x 31" (173 cm x 173 cm x 79 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.59+ Eprom Board 6600-042, Eprom Rev. 5.59+
Transformer:	120V - 12V 6560-274 (without) 6000-516 (with plug)
Heater:	1 kW 120V or 4.0 kW 240V heater 6000-338
Panel:	1-pump 680 panel 6600-652
Pump #1:	2.5HP 2-spd 240V 48F (6500-345) Pump mount (6000-532)
Pump #2:	N/A
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-159, 6000-742 and 6000-743
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-855
Circulation Pump:	N/A
12 Textured Jets:	4-DVX (2540-431), 8-DXL (2540-317)
Air Controls:	1 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	N/A
Hand Rails:	N/A
Filter:	35 sq ft 6000-136

Year:	2012
Model:	Denali
Size:	78" Round x 36" (198.1 cm Round x 91.5 cm)
Series:	680
Blower:	N/A
Board:	680 Series with 5.59+ Eprom Board 6600-042, Eprom Rev. 5.59+
Transformer:	120V - 12V 6560-274 (without) 6000-516 (with plug)
Heater:	1 kW 120V or 4.0 kW 240V heater 6000-338
Panel:	1-pump 680 panel 6600-652
Pump #1:	2.5HP 2-spd 240V 48F (6500-345) Pump mount (6000-532)
Pump #2:	N/A
Temp Sensor:	Curled Finger connector, thermistor type, resistance can be checked 6600-166
Hi-Limit:	Curled Finger connector, thermistor type, resistance can be checked 6600-144
Pressure Switch:	6560-869
Weir Gate:	Canister, basket and weir 6541-157, 6000-740 and 6000-741
Timer:	Electronic counter on circuit board
Sanitizer:	ClearRay Water Purification System 6472-855
Circulation Pump:	N/A
20 Textured Jets:	8-DX (2540-261), 4-DVX (2540-431), 7-DXL (2540-317), 1-Divert-a-jet (6541-800, 6541-797, 6540-511, 6540-798, 6540-796)
Air Controls:	3 - 6541-281 (knob), 6541-284 (manifold), 6541-282 (nut) 6541-283 (gasket)
Diverter:	N/A
Air Injectors:	N/A
Pillows	N/A
Hand Rails:	N/A
Filter:	50 sq ft 373045S